## AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

## LISTING OF CLAIMS



1. (Currently Amended) A computer-implemented method for embedding hidden data in an audio signal, comprising the steps of:

receiving the audio signal in a base domain;

transforming the received audio signal to a non-base domain one of a linear prediction residue domain and a cepstrum domain; and

embedding the hidden data in the transformed non-base domain one of the linear prediction residue domain and the cepstrum domain via parametric representation of the audio signal.

2. (Currently Amended) The method of Claim 1 further comprising the step of:

transforming the received audio signal to the non-base domain one of the linear prediction residue domain and the cepstrum domain such that transform domain coefficients are generated that are indicative of the transformed non-base domain audio signal.

3. (Currently Amended) The method of Claim 1 further comprising the steps of:

transforming the received audio signal to the non-base domain one of the linear prediction residue domain and the cepstrum domain such that transform domain coefficients are generated that are indicative of the transformed non-base domain audio signal; and

manipulating a statistical measure of a selected subset of the transform domain coefficients in order to embed the hidden data.

4. (Currently Amended) The method of Claim 3 further comprising the step of:

modulating the embedded data with at least one predetermined statistical feature of the transformed non-base domain audio signal.

5. (Currently Amended) The method of Claim 3 further comprising the step of:

increasing the amplitude of at least one predetermined feature of the transformed non-base domain audio signal so that statistical mean of the predetermined feature is positive for embedding a bit of one in the audio signal.

- 6. Cancelled.
- 7. Cancelled.

- 8. (Original) The method of Claim 1 further comprising the step of: using a psycho-acoustic model to control inaudibility of the embedded data.
- 9. (Currently Amended) The method of Claim 1 further comprising the steps of:

transforming the received audio signal to the non-base domain wherein the non-base domain is selected from the group consisting of linear prediction residue domain and cepstrum domain;

generating an inverse transformation signal using the embedded hidden data that is in the transformed non-base domain audio signal;

receiving an attack upon the generated inverse transformation signal;

transforming the attacked inverse transformation signal to the a non-base domain so as to generate a second transformed audio signal that is in the non-base domain; and

extracting the embedded hidden data from the second transformed audio signal that is in the non-base domain.

10. (Currently Amended) The method of Claim 1 further comprising the steps of:

transforming the received audio signal to a the cepstrum domain;

embedding the hidden data in the cepstrum domain; and

enforcing a positive mean to embed a "1" and keeping a zero mean intact to embed a "0" in the cepstrum domain.

Serial No. 09/499,525

11. (Currently Amended) A computer-implemented apparatus for embedding hidden data in an audio signal, comprising the steps of:

a data input device for receiving the audio signal in a base domain;

a signal transformer connected to the data input device for transforming the received audio signal to a non-base domain one of a linear prediction domain and a cepstrum domain; and

an embedder connected to the signal transformer for embedding the hidden data in the transformed non-base domain one of the linear prediction domain and the cepstrum domain of the audio signal.

12. (Currently Amended) The apparatus of Claim [[12]] 11 wherein the signal transformer transforms the received audio signal to the non-base domain such that transform domain coefficients are generated that are indicative of the transformed non-base domain audio signal, said embedder manipulating a statistical measure of a selected subset of the transform domain coefficients in order to embed the hidden data.

- 13. (Cancelled).
- 14. (Cancelled).
- 15. (Original) The apparatus of Claim 11 further comprising: a psycho-acoustic model to control inaudibility of the embedded data.

Serial No. 09/499,525

16. (Currently Amended) The apparatus of Claim 11 wherein the transformer transforms the received audio signal to a <u>the</u> cepstrum domain, said embedder embedding the hidden data in the cepstrum domain by enforcing a positive mean to embed a "1" and keeping a zero mean intact to embed a "0" in the cepstrum domain.

RI